

# 2019 BELL'S BEER BAYVIEW MACKINAC RACE

JULY 20<sup>TH</sup>, 2019

---

## Amendment No. 2 to Notice and Conditions of Race

The Monohull Safety Equipment Requirements are amended as follows (deletions/strikeouts or additions in bold red font):

- 2.6 Specific Requirements for Boats Less than 30'** – It is required that boats less than 30 feet (9.14m) shall meet the requirements of 2.4.2 through ~~2.5.1~~ **2.5** above and:
- (a) Shall have at least one lifeline with 18" (457 mm) minimum height above deck, and a maximum vertical gap of 18" (457 mm). Taller heights will require a second lifeline. The minimum diameter shall be 1/8" (3mm): or
  - (b) If not meeting the requirements of 2.4.1 through ~~2.5.1~~ **2.5** above herein, each crew member shall wear a safety harness and tether complying with section 3.1.3 below herein at all times while not in cabin, which tether shall be attached to a strong point on the boat.
- 2.7 Specific Requirements for boats 30' and over** - Boats 30' (9.14m) and over shall meet the requirements of 2.4.2 through ~~2.5.2~~ **2.5** above herein and:
- (a) Have at least two lifelines with 24" (762mm) minimum height above deck, and a maximum vertical gap of 15" (381mm). The minimum diameter will be 5/32" (4mm) for boats to 43' (13.1m) and 3/16" (5mm) for boats over 43' (13.1m).
- 6.1.3 PFD Equipment** - In addition to the requirements of sections 3.1.2 and ~~3.22~~ **3.23** above herein, it is STRONGLY RECOMMENDED that each PFD shall be equipped with crotch or leg straps, a whistle, a waterproof light, be fitted with marine-grade retroreflective material, and be clearly marked with the boat's or wearer's name, and be compatible with the wearer's safety harness. If the PFD is inflatable, it shall be regularly checked for air retention.

Robert Nutter  
2019 Bell's Beer Bayview Mackinac Race  
13-February 2019  
16:32